

CPVC Pipe & Threaded Fittings

CPVC Pipe

Sprinkler Pipe



Sizes	DN20 thru DN80 (3/4" thru 3")
Pipe Length	3.05m (10') Lengths
Approvals	UL, C-UL Listed & FM, MEA, NSF, Fire Academy of Russia, & LPCB Approved
Rated Pressure	12,1 bar (175 psi)
Maximum Temperature Rating	65°C (150°F).
Tech Data Sheet	TFP1915 and Installation Handbook - IH-1900

Manufactured with Lubrizol's BLAZEMASTER® compound ■ Produced from BlazeMaster® thermoplastic compound, RAPID RESPONSE CPVC pipe is designed exclusively for use in wet and dry pipe automatic fire sprinkler systems. ■ Our CPVC pipe is easier to install than traditional steel components, while providing superior heat resistance and strength compared to traditional CPVC and PVC piping materials. ■ TYCO CPVC sprinkler pipe conforms to the requirements of ASTM F442 and is produced to SDR 13.5. SDR (Standard Dimension Ratio) is the ratio of the outside pipe diameter to the wall thickness of the pipe.

CPVC Pipe												
Part No.	Size		OD mm	ID mm	Length m	Weight kg	Approval Listings					
	DN	In.					LPCB	FM	UL	MEA	NSF	Fire Academy of Russia
80300T	20	3/4"	26.7	22.7	3.05	0.6	✓	✓	✓	✓	✓	✓
80301T	25	1"	33.4	28.5	3.05	0.9	✓	✓	✓	✓	✓	✓
80302T	32	1-1/4"	42.1	35.9	3.05	1.4	✓	✓	✓	✓	✓	✓
80303T	40	1-1/2"	48.3	41.1	3.05	1.8	✓	✓	✓	✓	✓	✓
80304T	50	2"	60.3	51.4	3.05	2.9	✓	✓	✓	✓	✓	✓
80305T	65	2-1/2"	73.0	62.2	3.05	2.9	✓	✓	✓	✓	✓	
80306T	80	3"	88.9	75.7	3.05	6.3	✓	✓	✓	✓	✓	